

LISOFLOOR 950

Hardener and sealer for concrete floors



The green power
for your surface

LisoChem SRL

Rue de Le Mesnil, 34
5670 Viroinval
(Belgium)
Phone: +32 60 490 190
Mobile: +32 483 367 323
www.lisochem.com
info@lisochem.com

Manufacture & Office

Rue des Mousquetaires Gris
35 ZI de Mariembourg
5660 Belgium

CHARACTERISTICS

LisoFloor 950 is a hardener combining the latest generation of silicates.

PRODUCT DESCRIPTION

Combining potassium silicate with the latest developments in lithium silicate, this hardener can be sprayed onto new or old concrete.

An excellent dust suppressant, it increases surface hardness by 15 to 25% and provides exceptional waterproofing. This water-based solution is easy to use, does not require rinsing with water, and complies with VOC standards in force worldwide.

This product penetrates more deeply thanks to the small size of its potassium and lithium molecules. This product is also recommended for floors requiring a high polish to increase surface durability.

LISOFLOOR 950

Hardener and sealer for concrete floors

The Green Power for your surface

BENEFITS

- Lithium- and potassium-based products
- Hardener for new and old concrete surfaces
- Excellent abrasion resistance and dust resistance
- Water-based, solvent-free product with very low VOC emissions
- Suitable for concrete polishing processes and increases the durability of a polished finish

USE

Fresh concrete, new or old

SECURITY

Please refer to the safety data sheet :

- Keep out of reach of children
- Protect from freezing
- Wear gloves and safety glasses
- Cover all metal and glass parts before application

PROPERTIES

- Clear liquid
- Odorless
- pH : 12
- Density : 1.11
- Shelf life: 1 year in unopened original packaging

LISOFLOOR 950

Hardener and sealer for concrete floors

The Green Power for your surface

PREPARATION, APPLICATION, MAINTENANCE

General notes :

- Never apply in frost or rain. Always test on the substrate in an inconspicuous place.
- Never dilute or add other products or liquids to the base product. It is very important to mix the product thoroughly before and during use.

Preparation and application :

Never apply in frost or rain. Always test the surface in an inconspicuous place.

- Clean surface with vacuum cleaner or scrubber-dryer.
- Spray the product onto the surface (between 8 and 14 m²/L depending on the porosity of the concrete)
- Spread the product with a soft broom or micro-fiber brush
- Keep surface damp for 20 minutes
 - After 20 minutes, remove excess product
 - When dry, polish or sand surface

Please read the application system.

Maintenance : Clean the surface at least once a week with a scrubber-dryer and a neutral soap (LisoClean 820) during the first month of application, to increase hardness and resistance to stains such as oil, beverages, etc.

PACKAGING

Bucket20L

IBC 1000L