

LISOTOP 500

Water and oil repellent



The green power
for your surface

LisoChem SRL

Rue de Le Mesnil, 34
5670 Viroinval
(Belgium)
Phone: +32 60 490 190
Mobile: +32 483 367 323
www.lisochem.com
info@lisochem.com

Manufacture & Office

Rue des Mousquetaires Gris
35 ZI de Mariembourg
5660 Belgium
Phone: +32 60 490 190
Mobile: + 32 483 367 323



CHARACTERISTICS

LisoTop 500 is a colorless, waterproofing, oleophobic treatment for interior and exterior surfaces in natural stone, brick and concrete.

An oleophobic, waterproofing solution for all materials (bricks, concrete) and natural stone such as marble, bluestone, granite, ...

PRODUCT DESCRIPTION

LisoTop 500 is a high-performance fluoropolymer designed to give superior oil and water repellency to all interior and exterior concrete and masonry surfaces.

LisoTop 500 is non-toxic, odorless, water-based, non-flammable and easy to use.

LisoTop 500 reduces both freeze-thaw spalling and efflorescence, extending the life of the substrate.

A surface treated with LisoTop 500 that penetrates the material does not have a surface film that can be pelled off or removed, making it more durable.

LISOTOP 500

Water and oil repellent

The Green Power for your surface

BENEFITS

LisoTop 500 :

- Is a colorless, waterproofing, oil-repellent treatment for interior and exterior.
- Is a new exclusive based on latest-generation fluorinated polymers.
- Water-based product

USE

LisoTop 500 is used as an oil- and water-repellent impregnation for absorbent substrates such as concrete, brick, masonry and stone surfaces. It can be used for : driveways, patios, pavers, floors, sidewalks, concrete blocks, manufactured stone, walls, concrete surfaces.

SECURITY

Please refer to the safety data sheet:

- Keep out of reach of children
- Protect from freezing
- Wear gloves and safety glasses
- Cover all metal and glass parts before application

PROPERTIES

- Transparent
- Odorless
- pH : 4,5
- Density : 1,02
- Boiling point : 100°C
- Shelf life: 1 year in unopened original packaging

LISOTOP 500

Water & Oil repellent

The Green Power for your surface

PREPARATION, APPLICATION, MAINTENANCE

General notes :

- Never apply in frost or rain. Always test on the substrate in an inconspicuous place.
- Never dilute or add other products or liquids to the base product. It is very important to mix the product thoroughly before and during use.

Preparation and application :

Always test on the substrate in an inconspicuous place.

- LisoTop 500 should be applied using a low-pressure sprayer, airless, roller or brush.
- Apply 1 liter of product for 5 to 10 m². Yield varies according to surface porosity.
- Apply a first coat and, before drying, a second coat.
- Never leave an excess of product; wipe with a clean cloth before drying.
- For vertical surfaces, always apply the product from bottom to top.
- Maximum protection is achieved 3 to 6 days after treatment.

Please read the application system.

Care : Clean all equipment with water.

PACKAGING

Bucket20L

IBC.....1000L

Lisochem S.R.L. Tous droits réservés.
Date de révision : 15-05-2024