

LISOTOP 600

Waterproofing



The green power
for your surface

LisoChem SRL

Rue de Le Mesnil, 34
5670 Viroinval
(Belgium)
Phone: +32 60 490 190
Mobile: +32 483 367 323
www.lisochem.com
info@lisochem.com

Manufacture & Office

Rue des Mousquetaires Gris
35 ZI de Mariembourg
5660 Belgium
Phone: +32 60 490 190
Mobile: + 32 483 367 323

CHARACTERISTICS

LisoTop 600 is the perfect waterproofing product for concrete, brick, marble and stone.

- UV-resistant
- Pollution-resistant

PRODUCT DESCRIPTION

LisoTop 600 is a high-performance, water-based emulsion designed to impart superior waterproofing to all interior and exterior masonry (brick, natural stone) and concrete surfaces.

LisoTop 600 is non-toxic, odorless, water-based, non-flammable and easy to use.

LisoTop 600 reduces both freeze-thaw scaling and efflorescence, extending the life of the substrate.

LisoTop 600 is easy to apply.

LISOTOP 600

Waterproofing

The Green Power for your surface

BENEFITS

LisoTop 600 :

- Is a colorless, waterproofing treatment for all interior and exterior concrete and masonry surfaces.
- Is a new, exclusive water-based product.

USE

LisoTop 600 can be used on absorbent substrates such as concrete, brick and masonry.

SECURITY

Please refer to the safety data sheet :

- Keep out of reach of children
- Protect from freezing
- Wear gloves and safety glasses
- Cover all metal and glass parts before application

PROPERTIES

- Transparent or slightly yellowish liquid
- Odorless
- Density : 1,02
- pH : 12
- Boiling point : 100°C
- Shelf life: 1 year in original closed packaging

LISOTOP 600

Waterproofing

The Green Power for your surface

PREPARATION, APPLICATION, MAINTENANCE

General notes :

- Never apply in frost or rain. Always test on the substrate in an inconspicuous place.
- Never dilute or add other products or liquids to the base product. It is very important to mix the product thoroughly before and during use.

Preparation and application :

Always test on the substrate in an inconspicuous place.

- LisoTop 550 should be applied using a low-pressure sprayer, airless, roller or brush.
- Apply 1 liter of product for 5 to 10 m². Yield varies according to surface porosity.
- Apply a first coat and, before drying, a second coat.
- Never leave an excess of product; wipe with a clean cloth before drying.
- For vertical surfaces, always apply the product from bottom to top.
- Maximum protection is achieved 3 to 6 days after treatment.

Please read the application system.

Care : Clean all equipment with water.

PACKAGING

Bucket20L

IBC.....1000L

Lisochem S.R.L. Tous droits réservés.
Date de révision : 15-05-2024